

VideoX XM4W

4 Bay Rugged w/ 4x POE+ - Wide Temperature



32TB

Max Storage

24

Max Cameras

550Mb

Throughput

0 to 55C

Max Temp

VideoX XM4E

4 Bay Rugged w/ 4x POE+ - Extreme Temperature



32TB

Max Storage

24

Max Cameras

550Mb

Throughput

-40to70C

Max Temp

VideoX XM4W Rugged Mobile NVR POE+		VideoX XM4E Rugged Extreme NVR POE+
Intel® Core™ i3 Processor 4 Core Low TDP / 8GB DDR4 Memory	Processing	Intel® Core™ i3 Processor 4 Core Low TDP / 8GB DDR4 Memory
Up to: 32TB RAW. 4x SSD (500GB, 1GB, 2TB, 4TB or 8TB Ruggedized, SATA 6Gb/s 3.5" SDD's. Wide Temp	Video Storage	Up to: 32TB RAW. 4x SSD (500GB, 1GB, 2TB, 4TB or 8TB Ruggedized, SATA 6Gb/s 3.5" SDD's. - Extreme Temp
250GB Wide Temp V-NAND Flash SSD SATA3 M.2	System Storage	250GB Extreme Temp V-NAND Flash SSD SATA3 M.2
Dual 1Gbit Ethernet & 4x 1Gb POE+ RJ45 Copper ports	Networking	Dual 1Gbit Ethernet & 4x 1Gb POE+ RJ45 Copper ports
RAID Mirroring Fault Tolerance, or striping (capacities shown with JBOD)	RAID	RAID Mirroring Fault Tolerance / or striping (capacities shown with JBOD)
Intel UHD630 QuickSync GPU w/ GPU Tuned FW & Services	GPU	Intel UHD630 QuickSync GPU w/ GPU Tuned FW & Services
Microsoft Windows 10 Pro	OS	Microsoft Windows 10 Pro
6V to 36V DC-In, 3 Pin Terminal Block, 16 Mode Ignition Control 80V Surge Protection. AC 160W power adapter available	Power	6V to 36V DC-In, 3 Pin Terminal Block, 16 Mode Ignition Control 80V Surge Protection. AC 280W power adapter available
Ruggedized, mobile, fanless operation 260mm x 215mm x 104.1mm (10.24" x 8.46" x 4.10")	Physical	Ruggedized, mobile, fanless operation 260mm x 215mm x 104.1mm (10.24" x 8.46" x 4.10")
Ideal for Mobile Vehicles & Warehouses		Ideal for outdoor & surveillance trailers
3 Years Advanced Warranty with return to factory	Warranty	3 Years Advanced Warranty with return to factory
0°C to 55°C (32°F to 131°F) Operating. -40°C to 85°C (-40°F to 185°F) (non-operating) 5% to 95% Humidity, non-condensing	Temperature	-40°C to 70°C (-40°F to 160°F) (operating) -40°C to 85°C (-40°F to 185°F) (non-operating) 5% to 90% Humidity, non-condensing
IEC 60068-2-27, SSD: 50G @ wallmount, Half-sine, 11ms IEC 60068-2-64, SSD: 5Grms, 5Hz to 500Hz, 3 Axis	Shock/Vibe	IEC 60068-2-27, SSD: 50G @ wallmount, Half-sine, 11ms IEC 60068-2-64, SSD: 5Grms, 5Hz to 500Hz, 3 Axis
D-Sub, DVI-D and HDMI. (NOT Recommended to run video client on this server)	Video Display	D-Sub, DVI-D and HDMI. Supports Single Monitor (NOT Recommended to run video client on this server)
Milestone XProtect, Avigilon ACC7 or ONSSI Ocularis 5 Pre-loaded, GPU Active & Performance tuned.	VMS	Milestone XProtect, Avigilon ACC7 or ONSSI Ocularis 5 Pre-loaded, GPU Active & Performance tuned
6 USB 3.1, 4 COM RS-232/422/485, 16 ISOLATED DIO SIM SOCKETS FOR WIFI/4G/3G/LTE/GPRS/UMTS	Ports	6 USB 3.1, 4 COM RS-232/422/485, 16 ISOLATED DIO SIM SOCKETS FOR WIFI/4G/3G/LTE/GPRS/UMTS

